

# The Light Source

## TC Clamp



The TC Clamp will fasten from 2" OD to 1.5" OD tube. The TC Clamp has a 2-1/2" T-handle so no tools are required to fasten to the pipe. 1.25" x 1/2"-13 TPI Grade 8 fastener, Nylock Nut and 1" diameter Belleville Spring washer are provided for connecting your load. Dimensions: 4-5/8" T x 4"W x 1-3/16" thick. Safe Vertical Working Load 450 Pounds, (200 KG). Weight is 1.22 pounds (.55 KG)

**Minimum Size** 1.5" OD tube, 1.25" pipe, 1.66" OD pipe

**Maximum Size** 2" OD truss tube, 1.5" pipe, 1.90" OD

**Safe Vertical Working Load** 450 Pounds

**Hardware**

1.25" x 1/2" – 13 TPI Grade 8 fastener with Nylock nut.  
1" Belleville spring washer.

**Dimensions** 4 5/8" tall x 4" wide x 1 3/16" thick

**Weight** 1.25 lbs.

**Order Codes**

**TCSB** TC Clamp Swivel , Black Anodized

**TCB** TC Clamp, Black Anodized

**TCM** TC Clamp, Silver



輸入・販売元：

株式会社 テクニカル・サプライ・ジャパン

〒154-0014 東京都世田谷区新町1-21-16

TEL 03(3425)2400 FAX 03(3425)2402

Web : [www.tsjnet.co.jp](http://www.tsjnet.co.jp)